

## HKE-HD



### Contact

Judy Riddle  
 704-663-2490  
[jriddle@titanstrapping.com](mailto:jriddle@titanstrapping.com)



## Combined strapping tool for steel strap

### Minimal effort for high-performance strap

The HKE-HD is a special tool for using straps with a width of 19 mm and thickness from 0.6 to 0.8 mm. Processing such straps requires of course a little more effort than processing standard straps. The HKE-HD has a more voluminous body than its little brother, the HKE-L, to master the heavier loads with even more confidence. The longer levers make the job easier.

Apart from that, the typical HKE advantages are retained in the HD version: the TITAN-typical sealless joint with three notches is particularly suitable for flat packages.

Further advantages are the minimal risk of injury from this joint and the use of the HKE-HD in mobile applications. The HKE-HD is flexible enough for use in mobile applications.

### Technical Data

Kind of drive (tensioning)	Manually
Tension force	up to approx. 6,000 N
Kind of drive (sealing)	Manually
Dimensions	22.4 x 5.1 x 7.5" (L x W x H)
Weight	9.3 lb

### Strap/Joint

Type of strap	Steel strap
---------------	-------------

Strap	Automatenband up to approx. 900 N/mm <sup>2</sup> tensile strength MEGABAND® up to approx. 1.100 N/mm <sup>2</sup> tensile strength
Strap width	3/4"
Strap thickness	0.024 - 0.031"
Kind of seal	Sealless-joint
Sealing strength (depending on strap quality, strap dimensions)	to approx. 75% of the strap breaking load

#### **Minimum bearing area**

Flat package	5.9"
--------------	------

#### **Application**

Strapping of flat packages (e.g. palletized goods) for mobile use.
--