

SPZ



Contact

Judy Riddle
 704-663-2490
jriddle@titanstrapping.com



Pneumatic sealer for steel strap

"Simple" in two variants

If you need a simple steel strap sealer for circular and flat packages, the SPZ from TITAN is the best choice. To sum up its characteristics: Robust pneumatic technology, ergonomic design, a weight of just 3.3 kg and single-notch seal joint for seal types RSK / RSL 19, RSK / RSL 25 and RSK / RSL 32. Handling and operation are intuitive, and maintenance is very user-friendly. By the way: This simple tool is available in two variants:

Thanks to their different grip angles, SPZ-E and SPZ-W meet the needs of a wide range of users. The matching tensioner for the SPZ is the TITAN PR33; if one notch is not enough, you can resort to the TITAN DPZ-L with double notch.

Technical Data

Kind of drive (sealing)	Pneumatic
Seal (Type)	RSK, RSL
Dimensions	11.8 x 8.3 x 9.4" (L x W x H)
Weight	7.3 lb
Air pressure	max. 6 bar flow pressure

Strap/Joint

Type of strap	Steel strap
---------------	-------------

Strap	Automatenband MEGABAND [®]
Strap width	3/4" ; 1" ; 1 1/4"
Strap thickness	0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND [®])
Kind of seal	Seal-joint (single notch)

Application

Strapping of packages and palletized goods with small contact surfaces.