

## Bright Strap



### Contact

Edward McGinty  
704-663-2490  
sales@titanstrapping.com



## Packing Steel Strap

### Reduced to the essentials - inexpensive and good

In some application areas, the most cost-effective solution is needed.

For example, if no high demands are placed on the system breaking load. Using savings potentials is the motto when using blank strap. However, you do not have to do without the typical TITAN quality when using blank strap:

Blank strap has a waxed surface that prevents cold welding during processing with hand-held tools and stands thanks to the established rounding as well as its sibling products for minimal risk of injury. TITAN blank strap is the efficient and at the same time safe choice for short use, for example in wood processing and for building materials

### Technical Data

|                             |  |
|-----------------------------|--|
| Dimensions                  | from 12 x 0.38 mm to 32 x 1.00 mm<br>from 1/2 x 0.015" to 1 1/4 x 0.040"   |
| Tensile strength            | up to 600 N/mm <sup>2</sup>  |
| Breaking load approx.       | up to 19,000 N   4,300 lbf   |
| Elongation (A5) min approx. | ≥ 3%   |
| Surface                     | <b>blank:</b> surface like cold rolled strip with rolling emulsions or additional oil/ waxn<br><b>zinc plated:</b> on request, waxed |
|                             |  |

|                  |  |
|------------------|--|
| Coiling          | ribbon wound   |
| Form of delivery | skid pallets, frames for jumbo coils, special skids on request             |
| Certification    | quality management: DIN EN ISO 9001<br>energy management: DIN EN ISO 50001 |