

HKE-UL



Contact

Judy Riddle
704-663-2490
jriddle@titanstrapping.com



Combined strapping tool for steel strap

01 Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua.

02 At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

03 Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua.

04 At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

05 Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua.

Technical Data

Kind of drive (tensioning)	Manually
Tension force	up to approx. 6,000 N
Kind of drive (sealing)	Manually
Dimensions	18.7 x 4.5 x 7.5" (L x W x H)
Weight	5.7 lb

Strap/Joint

Type of strap	Steel strap
---------------	-------------

Strap	Automatenband up to approx. 900 N/mm ² tensile strength
Strap width	1/2"
Strap thickness	0.016 - 0.024 in
Kind of seal	Sealless-joint
Sealing strength (depending on strap quality, strap dimensions)	information currently not available

Minimum bearing area

Flat package	5.9 in
--------------	--------

Application

Strapping of flat packages (e.g. palletized goods) for mobile use.
--